

EXCEEDS: FEDERAL SPECIFICATION VV-P-216 AND MIL-L-3150-C

\$12.95

This exclusive formula has been engineered for use as a multi-functional penetrating, anti-wear, anti-corrosive lubricant. The film-forming barrier of protection provided by our penetrating lubricant reduces the need for frequent applications. [13oz aerosol](#)

Overall Benefits:

- Reduces** Friction, Wear
- Penetrates** Frozen Parts, Inaccessible Parts
- Provides** Extreme Pressure Protection

Applications:

Home Tools, Locks, Hinges, Fan Motors, Frozen Parts, Chains, Saw Blades, Air Tools, Latches, Industrial Chains, Cables, Bearings, Bushings, Linkage and more!

SPECIFICATIONS:

Flash Point (COC)	395 F
Pour Point	21 F
API Gravity @ 210F	24.1
Timken OK Load	60 lbs.
Viscosity SUS @ 210F	48.16
Viscosity Index	91
Falex E.P. Properties ASTM,D-3233 Equivalent True Load Failure	4200 lbs.
Falex Wear test ASTM D-2670 Number of Teeth of Wear 15 minutes at 910 Ft-Lb True Load	.0
4 Ball Wear Test ASTM, D-4066, Average Scar Diameter MM	0.54
Salt Sea Spray, 100 hours in 5% NaCl Solution Fog	No Rust



Directions for All Purpose Penetrating Spray Lubricant - APPL:

Spray lubricant on area to be treated. Let penetrate for several minutes.

For heavy rust formation, let lubricant penetrate overnight.

To prevent rust formation, do not wipe off.

CAUTION: KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Do not induce vomiting. Seek medical attention. Wash hands thoroughly with soap and water after use.